

Type	L #	Hits	Search Text	DBs	Time Stamp
1	BRS L4	63	((cable wire bus link) near3 (rate speed length)) with (adjust adjusted adjusting adjustment) with ((channel port pin interface) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:01
2	BRS L5	12	L4 and ((lowest slowest minimum) near3 (rate speed)) and ((maximum highest fastest) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:25
3	BRS L6	57	((cable wire bus link) near3 (rate speed length)) with (match matched matching) with ((channel port pin interface) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:02
4	BRS L7	407	((cable wire bus link) near3 (rate speed length)) with (reduce reduced reducing reduction increase increased increasing decrease decreased decreasing change changing changed) with ((channel port pin interface) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:13
5	BRS L8	4	6 and 7	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:09
6	BRS L9	53	6 not 8	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:09
7	IS&R L10	10407	((710/8,10,15,16,19,29,36,60,100,104,300,313) or (713/1,100)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:22
8	IS&R L11	2936	(710/2,62-64,72-74).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:22
9	BRS L12	910	(L10 and L11)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:22
10	BRS L13	12433	10 11	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:22
11	BRS L15	16	L4 and ((lower slower (less adj1 than)) near3 (rate speed)) and ((higher faster (more adj1 than)) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:31
12	BRS L16	0	12 and 14	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:32

10/675,678

	Type	L #	Hits	Search Text	DBs	Time Stamp
13	BRS	L17	3	13 and 14	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:33
14	BRS	L18	4	7 and 12	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:34
15	BRS	L19	29	7 and 13	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 17:34
16	BRS	L14	125	7 and ((lower slower (less adj1 than) lowest slowest minimum) near3 (rate speed)) and ((maximum highest fastest higher faster (more adj1 than)) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:58
17	BRS	L20	31	((cable wire bus) near3 (id identifier identification length)) with (reduce reduced reducing reduction increase increased increasing decrease decreased decreasing change changing changed adjust adjusted adjusting adjustment adjustable match matched matching) with ((channel port interface) near3 (bandwidth rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:22
18	BRS	L21	135	((cable wire bus) near3 (id identifier identification length)) same (reduce reduced reducing reduction increase increased increasing decrease decreased decreasing change changing changed adjust adjusted adjusting adjustment adjustable match matched matching) same ((channel port interface) near3 (bandwidth rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:22
19	BRS	L22	104	21 not 20	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:23
20	BRS	L23	35	22 and ((lower slower (less adj1 than) lowest slowest minimum) near3 (rate speed length)) and ((maximum highest fastest higher faster (more adj1 than)) near3 (rate speed bandwidth))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:32
21	BRS	L24	69	22 not 23	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:32

	Type	L #	Hits	Search Text	DBs	Time Stamp
22	BRS	L27	316	((speed rate bandwidth) near5 (port channel interface)) with (limit limiting limited) with ((speed rate length id identifier identification) near5 (cable bus link wire))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:57
23	BRS	L28	91	27 and ((lower slower (less adj1 than) lowest slowest minimum) near3 (rate speed bandwidth)) and ((maximum highest fastest higher faster (more adj1 than)) near3 (rate speed bandwidth))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 18:59
24	BRS	L29	0	12 and 28	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:04
25	BRS	L30	4	13 and 28	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:04
26	BRS	L31	225	27 not 28	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:04
27	BRS	L32	0	12 and 31	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:04
28	BRS	L33	12	13 and 31	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:07
29	BRS	L34	87	28 not 30	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:23
30	BRS	L35	213	31 not 33	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 19:23

Type	L #	Hits	Search Text	DBs	Time Stamp
1	IS&R L1	17	((("6640272") or ("6368155") or ("5836785") or ("20020041571") or ("5649001") or ("5513326") or ("5299944") or ("5671355") or ("5836785") or ("5909464") or ("5978569") or ("6032208") or ("6115678") or ("6226330") or ("6295519") or ("6317805") or ("6368155") or ("6434644") or ("20040153566"))).PN.	US-PGPUB; USPAT	2007/03/14 10:58
2	BRS L2	495	((cable wire bus link) near3 (length distance)) same ((rate speed)) same (channel port pin interface) same (configure configured reconfiguring reconfiguration reconfigure reconfigured reconfiguring reconfiguration re-configure re-configured re-configuring re-configuration)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 13:02
3	IS&R L3	10407	((710/8,10,15,16,19,29,36,60,100,104,300,313) or (713/1,100)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:49
4	IS&R L4	2936	(710/2,62-64,72-74).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:49
5	BRS L5	910	(L3 and L4)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:49
6	BRS L6	12433	L3 L4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:50
7	BRS L7	0	2 and 5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:50
8	BRS L8	13	2 and 6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:50
9	BRS L9	13941	((cable wire bus link) near3 (length distance)) and ((rate speed)) same (channel port pin interface) and (configure configured reconfiguring reconfiguration reconfigure reconfigured reconfiguring reconfiguration re-configure re-configured re-configuring re-configuration)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 11:57

10/675,678

Type	L #	Hits	Search Text	DBs	Time Stamp
10 BRS	L10	16	5 and 9	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:37
11 BRS	L11	2801	((cable wire bus link) near3 (length distance)) same ((rate speed)) same (channel port pin interface) same (set setting change changed changing reset re-set resetting re-setting)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:40
12 BRS	L12	1	5 and 11	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:27
13 BRS	L13	360	(6 and 9) not 10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:38
14 BRS	L14	14	(6 and 11) not 12	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:38
15 BRS	L15	50430	((cable wire bus link) near3 (length distance)) and ((rate speed)) and (channel port pin interface) and (set setting change changed changing reset re-set resetting re-setting)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:41
16 BRS	L17	559	(6 and 15) not 16	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:41
17 BRS	L16	37	5 and 15	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:41
18 BRS	L18	148	((cable wire bus link) near3 (length distance)) and ((rate speed) near3 effective) and (channel port pin interface) and (resetting)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:49
19 BRS	L19	0	5 and 18	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:50
20 BRS	L20	5	6 and 18	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:50
21 BRS	L21	0	((cable wire bus link) near3 (length distance)) with ((rate speed) near3 effective) with (channel port pin interface) with (resetting)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:52

Type	L #	Hits	Search Text	DBs	Time Stamp
22 BRS	L22	0	((cable wire bus link) near3 (length distance)) same ((rate speed) near3 effective) same (channel port pin interface) same (resetting)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 12:53
23 BRS	L23	63	((cable wire bus link) near3 (rate speed length)) with (adjust adjusted adjusting adjustment) with ((channel port pin interface) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 13:12
24 BRS	L24	9	23 and ((lowest slowest minimum) near3 (rate speed)) and ((maximum highest fastest) near3 (rate speed))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 13:24
25 BRS	L25	54	23 not 24	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2007/03/14 13:24